



PERMANENT FENCING

BARBED WIRE

Double-strand twisted wire with 2-point or 4-point barbs

Barbed wire is double-strand twisted fencing wire with sharp barbs at regular spacing, used on land boundaries, livestock fencing and security toppings. Leeter manufactures normal-twist and reverse-twist barbed wire in electro-galvanized, hot-dip galvanized and PVC-coated finishes, with strand and barb gauges built to your market.


SPECIFICATIONS

TYPE	Normal twist or reverse twist, double strand
STRAND × BARB GAUGE	10#×12#, 12#×12#, 12#×14#, 14#×14#, 14#×16#, 16#×16#, 16#×18# (SWG)
BARB SPACING	75–150mm (3"–6")
BARB LENGTH	15–30mm
FINISH	Electro-galvanized, hot-dip galvanized, PVC-coated
PVC OPTION	Core 1.0–3.5mm, coated OD 1.4–4.0mm, coating 0.4–0.6mm, colors available
COIL FORMAT	25–50kg coils or custom lengths, carton or woven-cloth wrapped

Specifications are indicative and produced to order — custom sizes, grades and finishes available.

KEY FEATURES

- Tight, even barb spacing from automated twisting lines
- Reverse-twist option locks barbs harder against rotation
- Hot-dip galvanized or PVC-over-galvanized for long field life
- Coil weight and length customized to your resale unit



APPLICATIONS

- Cattle and livestock fencing
- Land and crop boundary protection
- Security topping on chain link and panel fencing

ISO 9001

SGS AUDITED

BV SUPPLIER AUDIT

MILL TEST REPORTS

**LEETER**

WIRE · FASTENERS · SITE HARDWARE

ORDERING & EXPORTDOC LT-SPEC-BW-01 · Rev. Aug 2026 · www.leeter.cn

ORDERING REFERENCE

MOQ	Trial orders welcome — mixed containers supported
LEAD TIME	15–35 days after confirmed order
PAYMENT	T/T or L/C at sight
INCOTERMS	FOB Xingang / Tianjin, CIF on request
SAMPLES	Available — sample cost credited against order
PRIVATE LABEL	Custom cartons, labels and packaging (OEM)

PACKAGING & EXPORT

Coils wrapped with waterproof paper or woven cloth, palletized or floor-loaded.
Custom coil weights and private labels available. A container stuffing plan is supplied before shipment.

FREQUENTLY ASKED QUESTIONS

Which barbed wire gauge should I order?

The most traded export combinations are 12#×14# and 14#×14# SWG — heavy enough for livestock fence lines while keeping coil weight economical. Use heavier 10#–12# strands for high-tension boundary runs and lighter 16# combinations for security toppings.

What is the difference between normal twist and reverse twist?

Normal twist winds both strands in one continuous direction. Reverse twist alternates the twist direction between barbs, which locks the barbs more firmly and keeps the strands from unravelling when cut — preferred in many African and Middle East markets.

FACTORY-BACKED SUPPLY

Manufactured across 2 owned factories and 3 joint-venture plants operated by the Leeter / Five-Star Metals group, exporting construction wire and hardware since 2006 to North America, Europe and 5 continents.

HEAD OFFICE SALES & EXPORT

Room D808, ZhuoDa
Commercial Building,
Huai'an West Road,
Shijiazhuang, Hebei, China

CHINA FACTORY MANUFACTURING

Liusu Industrial Zone,
Dingzhou, Hebei, China

VIETNAM FACTORY FENCING PRODUCTION

Lot No. 610-612-614-789,
Binh Cang 2 Hamlet, Thu
Thua Commune, Tay Ninh
Province, Vietnam

HONG KONG OFFICE INTERNATIONAL TRADE

15/F, Konnect, 303 Jaffe
Road, Wan Chai, Hong Kong

WHAT TO INCLUDE IN YOUR RFQ

- Dimensions / gauge, grade and finish
- Quantity (e.g. 1 × 20ft container)
- Standard or drawing reference
- Packaging preference and private label
- Destination port and Incoterm

REQUEST A QUOTE

Send your specification, quantity and destination — we reply with price, packing and lead time within one business day.

SALES@LEETER.CN