

PERMANENT FENCING

CHAIN LINK FENCE FABRIC

Woven diamond-mesh rolls in galvanized or PVC-coated finish

Chain link fence fabric is woven diamond mesh supplied in rolls for permanent perimeter fencing. Leeter manufactures chain link in 3/4" to 4" mesh with 18-8 BWG wire, electro-galvanized, hot-dip galvanized or PVC-coated, with twisted or knuckled selvage to order.


SPECIFICATIONS

MESH OPENING	3/4"-4" (20×20 – 100×100mm)
WIRE DIAMETER	18-8 BWG (1.2-4.0mm)
HEIGHT	0.5-4.0m (4 ft / 5 ft / 6 ft standard)
ROLL LENGTH	10 / 15 / 20 / 25m (50 ft standard US roll)
SELVAGE	Twisted (barbed) or knuckled ends
FINISH	Electro-galvanized, hot-dip galvanized, PVC-coated (green/black)
POPULAR SIZES	50×50mm × 1.8mm and 60×60mm × 2.0mm, 25m rolls

Specifications are indicative and produced to order — custom sizes, grades and finishes available.

KEY FEATURES

- Uniform diamond weave for consistent tension on installation
- Twisted or knuckled selvage to match your market standard
- PVC coating over galvanized core for coastal and high-visibility runs
- Rolls compressed and wrapped for efficient container loading



APPLICATIONS

- Commercial and residential perimeter fencing
- Sports fields, playgrounds and highway or railway lines
- Airports, ports and utility enclosures

ISO 9001

SGS AUDITED

BV SUPPLIER AUDIT

MILL TEST REPORTS

**LEETER**

WIRE · FASTENERS · SITE HARDWARE

ORDERING & EXPORTDOC LT-SPEC-CLF-01 · Rev. Aug 2026 · www.leeter.cn

ORDERING REFERENCE

MOQ	Trial orders welcome — mixed containers supported
LEAD TIME	15–35 days after confirmed order
PAYMENT	T/T or L/C at sight
INCOTERMS	FOB Xingang / Tianjin, CIF on request
SAMPLES	Available — sample cost credited against order
PRIVATE LABEL	Custom cartons, labels and packaging (OEM)

PACKAGING & EXPORT

Rolls compacted, wrapped at both ends and strapped; palletized or floor-loaded to container. Loading plan on request. A container stuffing plan is supplied before shipment.

FREQUENTLY ASKED QUESTIONS

What is the difference between twisted and knuckled chain link?

Knuckled selvage folds the wire ends back into a smooth loop — the safe choice for schools, playgrounds and residential fencing. Twisted (barbed) selvage leaves sharp twisted ends at the top for added security on commercial and industrial perimeters. We supply either, or knuckled bottom with twisted top.

Which chain link mesh size and gauge should I order?

The workhorse combinations are 50×50mm (2") mesh with 1.8–3.0mm wire and 60×60mm with 2.0mm wire. Smaller 20–40mm mesh suits security and animal control; heavier 8–10 BWG wire suits high-abuse commercial runs. Tell us the fence height and use and we will match mesh and gauge.

Do you supply PVC-coated chain link?

Yes — PVC-coated chain link over a galvanized core, typically 50×50 or 60×60mm mesh with 1.8/2.8mm to 2.0/3.0mm core/overall diameters, in green, black or custom colors, 0.5–3m widths and 10–25m rolls.

FACTORY-BACKED SUPPLY

Manufactured across 2 owned factories and 3 joint-venture plants operated by the Leeter / Five-Star Metals group, exporting construction wire and hardware since 2006 to North America, Europe and 5 continents.

HEAD OFFICE SALES & EXPORT

Room D808, ZhuoDa
Commercial Building,
Huai'an West Road,
Shijiazhuang, Hebei, China

CHINA FACTORY MANUFACTURING

Liusu Industrial Zone,
Dingzhou, Hebei, China

VIETNAM FACTORY FENCING PRODUCTION

Lot No. 610-612-614-789,
Binh Cang 2 Hamlet, Thu
Thua Commune, Tay Ninh
Province, Vietnam

HONG KONG OFFICE INTERNATIONAL TRADE

15/F, Konnect, 303 Jaffe
Road, Wan Chai, Hong Kong

WHAT TO INCLUDE IN YOUR RFQ

- Dimensions / gauge, grade and finish
- Quantity (e.g. 1 × 20ft container)
- Standard or drawing reference
- Packaging preference and private label
- Destination port and Incoterm

REQUEST A QUOTE

Send your specification, quantity and destination — we reply with price, packing and lead time within one business day.

SALES@LEETER.CN